



WMD 020



Housing : Die cast aluminium body finished in black color
Painting : Polyester powder coated
Gasket : Weatherproof and durable silicone rubber
Front Glass : Clear toughened safety glass
Cable Entry : Silicone rubber grommet
Fastening : All external screws are made of stainless steel
Control Gear : Remote transformer in waterproof box for MR16 lamp
Mounting : Die cast aluminium bracket is provided for ease installation

MR 16/50 W		Spot type	
■ Illuminance Cone	lx	m.	
∅0.17	6750	1	
∅0.35	1687	2	
∅0.50	751	3	
∅0.70	423	4	



MR 16/50 W		Flood type	
■ Illuminance Cone	lx	m.	
∅0.35	5170	0.5	
∅0.70	1339	1	
∅1.40	333	2	
∅2.10	150	3	





 **2xMR16 /GX5.3** 20W / 35W / 50W |
  **2xPAR16 /GU10** 50W |
  blue / white / warm white / cool white / red / amber / green

WMD 021







Housing : Die cast aluminium body finished in black color
Painting : Polyester powder coated
Gasket : Weatherproof and durable silicone rubber
Front Glass : Clear toughened safety glass
Cable Entry : Black color silicone rubber grommet
Fastening : All external screws are made of stainless steel
Control Gear : Remote transformer in waterproof box for MR16 lamp
Mounting : Die cast aluminium bracket is provided for ease installation

PAR 20/50 W		Spot type	
■ Illuminance Cone	lx	m.	
∅0.10	11316	0.5	
∅0.17	2944	1	
∅0.35	736	2	
∅0.50	331	3	



PAR 20/50 W		Flood type	
■ Illuminance Cone	lx	m.	
∅0.25	3864	0.5	
∅0.54	1012	1	
∅1.00	253	2	
∅2.60	110	3	





 **2xGLS /E27** 60W |
  **2xMR16 /GX5.3** 25W / 35W / 50W |
  **2xPAR16 /GU10** 50W |
  **2xPAR20 /E27** 50W

WMD 022



Housing : Die cast aluminium body finished in black color
Painting : Polyester powder coated
Gasket : Weatherproof and durable silicone rubber
Front Glass : Clear toughened safety glass
Cable Entry : Black color silicone rubber grommet
Fastening : All external screws are made of stainless steel
Mounting : Die cast aluminium bracket is provided for ease installation

PAR 30/75 W		Spot type	
■ Illuminance Cone	lx	m.	
∅0.10	26496	0.5	
∅0.17	6900	1	
∅0.35	1720	2	
∅0.50	763	3	



PAR 30/75 W		Flood type	
■ Illuminance Cone	lx	m.	
∅0.25	8464	0.5	
∅0.54	2208	1	
∅1.00	552	2	
∅2.60	248	3	



 **2xPAR30 /E27** 75W / 100W |
  **2xTCT-EL /E27** 5W / 8W / 11W (Max length 117 mm.)



Accessories
Waterproof box



Installation Guide

