


WMS 041



Housing : Die cast aluminium body finished in black color
Painting : Polyester powder coated
Gasket : Weatherproof and durable silicone rubber
Front Glass : Clear toughened safety glass
Cable Entry : Black color silicone rubber grommet
Fastening : All external screws are made of stainless steel
Control Gear : Remote transformer in waterproof box for MR16 lamp
Mounting : Aluminium bracket is provided for ease installation

MR 16/50 W		Spot type	
■ Illuminance Cone	lx	m.	
∅0.17	6750	1	
∅0.35	1687	2	
∅0.50	751	3	
∅0.70	423	4	

MR 16/50 W		Flood type	
■ Illuminance Cone	lx	m.	
∅0.35	5170	0.5	
∅0.70	1339	1	
∅1.40	333	2	
∅2.10	150	3	



MR16 /GX5.3 20W / 35W / 50W | PAR16 /GU10 50W | PAR20 /E27 50W


WMD 041



Housing : Die cast aluminium body finished in black color
Painting : Polyester powder coated
Gasket : Weatherproof and durable silicone rubber
Front Glass : Clear toughened safety glass
Cable Entry : Black color silicone rubber grommet
Fastening : All external screws are made of stainless steel
Control Gear : Remote transformer in waterproof box for MR16 lamp
Mounting : Aluminium bracket is provided for ease installation

MR 16/50 W		Spot type	
■ Illuminance Cone	lx	m.	
∅0.17	6750	1	
∅0.35	1687	2	
∅0.50	751	3	
∅0.70	423	4	

MR 16/50 W		Flood type	
■ Illuminance Cone	lx	m.	
∅0.35	5170	0.5	
∅0.70	1339	1	
∅1.40	333	2	
∅2.10	150	3	



2xMR16 /GX5.3 20W / 35W / 50W | 2xPAR16 /GU10 50W | 2xPAR20 /E27 50W


WMS 042




Housing : Die cast aluminium body finished in black color
Painting : Polyester powder coated
Gasket : Weatherproof and durable silicone rubber
Front Cover : Clear toughened safety glass
Cable Entry : Black color silicone rubber grommet
Fastening : All external screws are made of stainless steel
Mounting : Aluminium bracket is provided for ease installation

PAR 30/75 W		Spot type	
■ Illuminance Cone	lx	m.	
∅0.10	26496	0.5	
∅0.17	6900	1	
∅0.35	1720	2	
∅0.50	763	3	

PAR 30/75 W		Flood type	
■ Illuminance Cone	lx	m.	
∅0.25	8464	0.5	
∅0.54	2208	1	
∅1.00	552	2	
∅2.60	248	3	



GLS /E27 60W / 100W | TCT-EL /E27 5W / 8W / 11W (Max length 117 mm.) | PAR30 /E27 75W / 100W



Installation Guide

