




GDS 030 - GDS 031



Housing : Die cast aluminium body finished in black color
Front Cover : Flat cover made of die cast aluminium finished in black color
Painting : Polyester powder coated
Gasket : Weatherproof and durable silicone rubber
Front Glass : Clear toughened safety glass
Cable Entry : Silicone rubber grommet with cable VDE 3x0.75 mm² ,1 M long
Fastening : All external screws are made of stainless steel
Control Gear : Remote transformer in waterproof box for MR16 lamp
Lamp Adjustment : Fully adjustable bracket allowing 360° rotation and 0-90° elevation
Mounting : Ground spike made of die cast aluminium



MR 16/50 W		Spot type	
■ Illuminance Cone	lx	m.	
ø0.70	423	4	
ø0.50	751	3	
ø0.35	1687	2	
ø0.17	6750	1	

MR 16/50 W		Flood type	
■ Illuminance Cone	lx	m.	
ø2.10	150	3	
ø1.40	333	2	
ø0.70	1339	1	
ø0.35	5170	0.5	



MR16 /GX5.3 20W / 35W / 50W | PAR16 /GU10 50W | blue / white / warm white / cool white / red / amber / green

GDS 041



Housing : Die cast aluminium or fiber glass body finished in black color
Front Cover : Cut-off glare shield made of die cast aluminium or fiber glass finished in black color
Painting : Polyester powder coated
Gasket : Weatherproof and durable silicone rubber
Front Glass : Clear toughened safety glass
Cable Entry : PG 9 brass cable gland with cable VDE 3x0.75 mm² ,1 M long
Fastening : All external screws are made of stainless steel
Control Gear : Remote transformer in waterproof box for MR16 lamp
Lamp Adjustment : Fully adjustable bracket allowing 360° rotation and 0-90° elevation
Mounting : Removable ground spike made of die cast aluminium



MR 16/50 W		Spot type	
■ Illuminance Cone	lx	m.	
ø0.70	423	4	
ø0.50	751	3	
ø0.35	1687	2	
ø0.17	6750	1	

MR 16/50 W		Flood type	
■ Illuminance Cone	lx	m.	
ø2.10	150	3	
ø1.40	333	2	
ø0.70	1339	1	
ø0.35	5170	0.5	



MR16 /GX5.3 20W / 35W / 50W | PAR16 /GU10 50W | blue / white / warm white / cool white / red / amber / green

GDS 051



Housing : Die cast aluminium or fiber glass body finished in black color
Front Cover : Cross glare shield made of die cast aluminium or fiber glass finished in black color
Painting : Polyester powder coated
Gasket : Weatherproof and durable silicone rubber
Front Glass : Clear toughened safety glass
Cable Entry : PG 9 brass cable gland with cable VDE 3x0.75 mm² ,1 M long
Fastening : All external screws are made of stainless steel
Control Gear : Remote transformer in waterproof box for MR16 lamp
Lamp Adjustment : Fully adjustable bracket allowing 360° rotation and 0-90° elevation
Mounting : Removable ground spike made of die cast aluminium



MR 16/50 W		Spot type	
■ Illuminance Cone	lx	m.	
ø0.70	423	4	
ø0.50	751	3	
ø0.35	1687	2	
ø0.17	6750	1	

MR 16/50 W		Flood type	
■ Illuminance Cone	lx	m.	
ø2.10	150	3	
ø1.40	333	2	
ø0.70	1339	1	
ø0.35	5170	0.5	



MR16 /GX5.3 20W / 35W / 50W | PAR16 /GU10 50W | blue / white / warm white / cool white / red / amber / green

